

## Design

Tiree CF650  
by Bute Design Studio.

## Application

Woven upholstery fabric  
suitable for both heavy duty  
and domestic applications.

## Composition

92% pure new wool, 8% nylon.

## Fabric Weight

960g/linear metre, 685g/m<sup>2</sup> approx.

## Fabric Width

140cm approx. standard usable width.

## Fabric Length

Lengths controlled and registered  
by calibrated measuring devices.

## Abrasion Resistance

Martindale, BS 2543:2004  
BS EN 14465:2003 – Annex A  
50,000 cycles.

## Flame Retardancy

Passes BS EN 1021 - 1 and 2:2006:  
Ignition Sources 0 and 1, and BS5852:  
2006: Section 4: Ignition Source 5.  
Also satisfies the requirements of  
BS7176: 2007: Medium Hazard  
category, direct testing route, when  
used in combination with a standard  
CMHR 35kg /m<sup>3</sup> polyurethane foam.  
This does not preclude passes over  
different types or densities of foam.

## Passes Crib 5

Passes IMO resolution  
A. 652 (16)

Passes Curtain and Drape  
BS5867 Part 2 Level B

## Light Fastness

Colours comply with the requirements  
of BS EN ISO 105 – B02:2013

## After Care

Regular maintenance greatly extends  
the useful life of a fabric. Ask for details  
of cleaning recommendations or consult  
a professional cleaning organisation.

## Special Requirements

Customised shades can be produced  
to meet individual requirements. Our  
Design Studio also collaborates in the  
development of special fabrics to fulfill  
aesthetic or fitness-for-purpose criteria.

## Ongoing Development

It is our policy to promote continuous  
product development and we therefore  
reserve the right to change technical  
fabrics from the Bute Collection without  
prior notice.

Bute Fabrics Ltd is an accredited BS EN ISO 9001:2008  
company. ISO 14001 Environmental Management System.

Wool is a natural fibre and is fully recyclable.  
Made in Scotland

## Enquiries

T +44 (0)1700 503 734  
F +44 (0)1700 504 545

sales@butefabrics.com  
butefabrics.com